

Tap and Drill




AVAILABLE FROM
NEPEAN ELECTRONICS

NEPEAN Power is a proven leader in the supply and manufacture of quality engineered solutions, products and technologies. Established in 1994, through the commitment of our dedicated team we have become a supplier of choice.

Drill					
Fully Ground Coffee Color HSS-Cobalt Straight Shank Twist Drill					
Part Number	Description	Shank (mm) (d)	Thread Length (mm) (l)	Overall Length (mm) (L)	
SSTD-2.0	M35 Cobalt Drill. 2.0mm. Metric DIN 338.	2.0	24	49	
SSTD-2.5	M35 Cobalt Drill 2.5mm. Metric DIN 338.	2.5	30	57	
SSTD-3.0	M35 Cobalt Drill. 3.0mm. Metric DIN 338.	3.0	33	61	
SSTD-3.1	M35 Cobalt Drill. 3.1mm. Metric DIN 338.	3.1	36	65	
SSTD-3.2	M35 Cobalt Drill. 3.2mm. Metric DIN 338.	3.2	36	65	
SSTD-3.3	M35 Cobalt Drill. 3.3mm. Metric DIN 338.	3.3	36	65	
SSTD-3.5	M35 Cobalt Drill. 3.5mm. Metric DIN 338.	3.5	39	70	
SSTD-4.0	M35 Cobalt Drill. 4.0mm. Metric DIN 338.	4.0	43	75	
SSTD-4.2	M35 Cobalt Drill. 4.2mm. Metric DIN 338.	4.2	43	75	
SSTD-4.5	M35 Cobalt Drill. 4.5mm. Metric DIN 338.	4.5	47	80	
SSTD-4.8	M35 Cobalt Drill. 4.8mm. Metric DIN 338.	4.8	52	86	
SSTD-4.9	M35 Cobalt Drill. 4.9mm. Metric DIN 338.	4.9	52	85	
SSTD-5.0	M35 Cobalt Drill. 5.0mm. Metric DIN 338.	5.0	52	86	
SSTD-5.5	M35 Cobalt Drill. 5.5mm. Metric DIN 338.	5.5	57	93	
SSTD-6.0	M35 Cobalt Drill. 6.0mm. Metric DIN 338.	6.0	57	93	
SSTD-6.5	M35 Cobalt Drill. 6.5mm. Metric DIN 338.	6.5	63	101	
SSTD-6.8	M35 Cobalt Drill. 6.8mm. Metric DIN 338.	6.8	69	109	
SSTD-7.0	M35 Cobalt Drill. 7.0mm. Metric DIN 338.	7.0	69	109	
SSTD-7.5	M35 Cobalt Drill. 7.5mm. Metric DIN 338.	7.5	69	109	
SSTD-8.0	M35 Cobalt Drill. 8.0mm. Metric DIN 338.	8.0	75	117	
SSTD-8.5	M35 Cobalt Drill. 8.5mm. Metric DIN 338.	8.5	75	117	
SSTD-9.0	M35 Cobalt Drill. 9.0mm. Metric DIN 338.	9.0	81	125	
SSTD-9.5	M35 Cobalt Drill. 9.5mm. Metric DIN 338.	9.5	81	125	
SSTD-10.0	M35 Cobalt Drill. 10.0mm. Metric DIN 338.	10	87	133	
SSTD-10.2	M35 Cobalt Drill. 10.2mm. Metric DIN 338.	10.2	87	133	
SSTD-10.5	M35 Cobalt Drill. 10.5mm. Metric DIN 338.	10.5	87	133	
SSTD-11.0	M35 Cobalt Drill. 11.0mm. Metric DIN 338.	11	94	142	
SSTD-11.5	M35 Cobalt Drill. 11.5mm. Metric DIN 338.	11.5	94	142	
SSTD-12.0	M35 Cobalt Drill. 12.0mm. Metric DIN 338.	12	101	151	
SSTD-12.5	M35 Cobalt Drill. 12.5mm. Metric DIN 338.	12.5	101	151	
SSTD-13.0	M35 Cobalt Drill. 13.0mm. Metric DIN 338.	13	101	151	
SSTD-13.5	M35 Cobalt Drill. 13.5mm. Metric DIN 338.	13.5	108	160	
SSTD-14.0	M35 Cobalt drill 14.0mm. Metric DIN 338.	14	108	160	
SSTD-16.0	M35 Cobalt drill 16.0mm. Metric DIN 338.	16	120	178	
SSTD-16.5	M35 Cobalt Drill 16.5mm. Metric DIN 338.	16.5	125	184	

Tap and Drill



Tap

HSS Ground Thread,ISO 529 Straight Flute Tap

Part Number	Description	Size	Shank (mm)	Thread Length (mm)	Overall Length (mm)
STFT-M3-T	ISO.M3 x 0.5mm Straight flute Tap.Taper Tap	M3X0.5	3.15	11	48
STFT-M4-T	ISO.M4 x 0.7mm Straight flute Tap. Taper Tap	M4X0.7	4	13	53
STFT-M5-T	ISO.M5 x 0.8mm Straight flute Tap. Taper Tap	M5X0.8	5	16	58
STFT-M6-T	ISO.M6 x 1.0mm Straight flute Tap. Taper Tap	M6X1	6.3	19	66
STFT-M8-T	ISO.M8 x 1.25mm Straight flute Tap. Taper Tap	M8X1.25	6.3	22	72
STFT-M10-T	ISO.M10 x 1.5mm Straight flute Tap. Taper Tap	M10X1.5	8	24	80
STFT-M12-T	ISO.M12x1.75mm Straight flute Tap.Taper Tap	M12X1.75	9	29	89



A



B



C




D



E

Photo	Item	Part Number	Description
A	Cutting Wheel	RBCW1251222	Resin bond cutting wheel for cutting inox,size125x1.2x22mm,abrasive:A,C,WA 70m/s,80m/s,Flat type
B	Grinding Wheel	RBGW125622	Resin bond grinding wheel, size125x6x22mm,abrasive:A,C,WA 70m/s,80m/s,Depressed type
C	Flap Disc	FD12522	Flap disc, size 125*22,abrasive:A,C,ZA. Grit 36#-400#.Conical.
D	Hole Saw	BMHS4216	Bi-metal hole saw, M42,Size 16
		BMHS4220	Bi-metal hole saw, M42,Size 20
		BMHS4225	Bi-metal hole saw, M42,Size 25
		BMHS4230	Bi-metal hole saw, M42,Size 30
		BMHS4232	Bi-metal hole saw, M42,Size 32
		BMHS4240	Bi-metal hole saw, M42,Size 40
		BMHS4265	Bi-metal hole saw, M42,Size 65
E	Arbor/ Pilot Drill/ Adaptor	BMHSAPA2	Bi-Metal Hole Saw Fit arbors, pilot drill, adaptor, M42 Shank size 7/16" Hex, Thread Size 5/8"-18UNF, Fit hole saws 1-1/4" to 6".



NEPEAN
Power

www.nepeanpower.com

For more information please contact:

P: +61 2 4088 2790

E: power@nepean.com